



Codan 2802 - ISO 3821:2019

Lätt, flexibel, slät, blå slang för syre, enligt EN ISO 3821:2019. För användning med industri autogen svetsutrustning, vanligtvis tillsammans med röd acetylslang. Även idealisk för naturgas och luft.

Type nr: 2802
Typ: Oxygen
Standard Längd: 50 meter
Arbets Temperatur: -30°C till 80°C
Insida: SBR/EPDM
Färg: Svart
Förstärkning: PVA
Utsida: EPDM
Färg: Blå
Standard: ISO 3821:2019
Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Vikt (g/m)	Product code
6,3	13,3	20	60	63	146	2802006000
10,0	17,0	20	60	100	203	2802010000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.