



Codan 2808 - EN ISO 3821:2019

Flexibel dubbelslang för propan/butan och syrgas. Det delande spåret möjliggör enkel separation. Speciellt utformad för industriell skärning och svetsuppgifter.

Type nr. 2808

Typ: Oxygen / LPG (Propan/Butan)

Standard Längd: 50 meter

Arbets Temperatur: -25°C till 80°C

Insida: NBR

Färg: Svart

Förstärkning: PVA

Utsida: SBR

Färg: Blå/Orange

Standard: EN ISO 3821:2019

Std. branding: -

Insida dia. (mm)	Utsida dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Vikt (g/m)	Product code
10,0	17,0	20	60	120	760	2808909000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.